



Thecnical data sheet



Cotton flap system flat mop

Cotton flat mop, looped end internal and cut end external, polyester support

| Technical information | | | | | | | |
|--|---|--|--|----------------------------|-----------------------------|----------------------------------|-------|
| code note | S | Weight/gr | cm,sizes | Box | pcs | kg | m3 |
| CMS40F Cotto | on Mop Standart Flap System | 125 | 40x14 | | 75 | 10,5 | 0,052 |
| CMS50F Cotto | on Mop Standart Flap System | 160 | 50x16 | | 50 | 10,5 | 0,052 |
| USAGE Flat mopping system with flaps, to be used either pre-soaked, soaked on demand with soaking station or with handles with tank Ideal for any surface and for particle dirt thanks to the high dirt collection power of yarn | | | | | | | |
| Easy: mop changing is easTouch-free: the detaching | | g system avoids any contact with the dirt ing surface and the possibility of reaching corners and cleaning under furniture | | | | | |
| MATERIAL Yarn: 70% cotton, 30% polyes | | ter - Support: po | lyester | | | | |
| INSTRUCTIONS | Washing temperature max 90' Bleaching possible, do not use Do not tumble dry or in a drye Follow the washing instruction Perform a pre-wash in cold wa operations. Recommended us Do not use laundry detergents | chlorine or ns (temperatures ater without laur e of professional | and dosage) on t dry detergent to textile laundry de | remove any etergent. Do | residual pro not use fak | oduct used during oric softener. | - |

RELATED PRODUCTS